

Applied Textiles Lab Services
 555 76th Street · Byron Center, MI 49315
 Phone: 616-559-6123 · Fax: 616-559-6119 · Email: testlab@applied-textiles.com
 TESTING SUBMITTAL FORM


Company: _____ Contact: _____
 Address _____ Email Address: _____
 Phone Number: _____ Fax Number _____

Flammability Tests:

ASTM E84	<input type="checkbox"/> Unadhered	<input type="checkbox"/> Adhered to GRC	<input type="checkbox"/> Adhered to Gypsum
ASTM E662 Smoke Density	<input type="checkbox"/>		
BIFMA 45 Degree Screening	<input type="checkbox"/>		
BIFMA Cigarette Ignition	<input type="checkbox"/>		
Boston BFD IX-1	<input type="checkbox"/>		
California Technical Bulletin 117, Sec. E	<input type="checkbox"/>		
California Title 19, Section 1237.1 Small Scale	<input type="checkbox"/>		
FAR 25.853 – 12 Second Vertical Test	<input type="checkbox"/>		
FAR 25.853 – 60 Second Vertical Test	<input type="checkbox"/>		
FAR 25.853 – Horizontal Test	<input type="checkbox"/>		
FAR 25.853 – 45 Degree Test	<input type="checkbox"/>		
FAR 25.853 – 60 Degree Test	<input type="checkbox"/>		
FMVSS 302	<input type="checkbox"/>		
NFPA 260	<input type="checkbox"/>		
NFPA 701 Small Scale – 1989	<input type="checkbox"/>		
NFPA 701 Large Scale – 1989	<input type="checkbox"/> Flat Method	<input type="checkbox"/> Folded Method	
NFPA 701 Test #1	<input type="checkbox"/> 2004	<input type="checkbox"/> 1999	<input type="checkbox"/> 1996
NFPA 701 Test #2	<input type="checkbox"/> 2004 – Flat Method	<input type="checkbox"/> 2004 – Folded Method	
	<input type="checkbox"/> 1999 – Flat Method	<input type="checkbox"/> 1999 – Folded Method	
	<input type="checkbox"/> 1996 – Flat Method	<input type="checkbox"/> 1996 – Folded Method	
New York City Bulletin #44	<input type="checkbox"/>		
NY/NJ Port Authority	<input type="checkbox"/>		
UFAC	<input type="checkbox"/>		

Physical Tests:

Breaking Strength <i>ASTM D5034</i>	<input type="checkbox"/>			
Brush Pill <i>ASTM D3511</i>	<input type="checkbox"/>			
Bursting Strength <i>ASTM D3787</i>	<input type="checkbox"/>			
Colorfastness to Drycleaning <i>AATCC 132</i>	<input type="checkbox"/>			
Colorfastness to Laundering <i>AATCC 61</i>	<input type="checkbox"/> Temperature:	<input type="checkbox"/> 105 (1A)	<input type="checkbox"/> 120 (2A)	<input type="checkbox"/> 160 (3A)
Colorfastness to Light <i>AATCC 16, Opt. 3</i>	<input type="checkbox"/> Hours:			
Colorfastness to Light <i>QUV ASTM G154</i>	<input type="checkbox"/> Hours:			
Colorfastness to Perspiration <i>AATCC 15</i>	<input type="checkbox"/>			
Colorfastness to Solvent <i>AATCC 107</i>	<input type="checkbox"/>			
Colorfastness to Water <i>AATCC 107</i>	<input type="checkbox"/>			
Colorfastness to Water: Sea <i>AATCC 106</i>	<input type="checkbox"/>			
Colorfastness to Water: Chlorinated Pool <i>AATCC 162</i>	<input type="checkbox"/>			
Dimensional Change <i>ASTM D3597</i>	<input type="checkbox"/>			
Dimensional Change to Drycleaning <i>AATCC 158</i>	<input type="checkbox"/>			



Applied Textiles Lab Services
 555 76th Street · Byron Center, MI 49315
 Phone: 616-559-6123 · Fax: 616-559-6119 · Email: testlab@applied-textiles.com

TESTING SUBMITTAL FORM

Dimensional Change to Commercial Laundering <i>AATCC 96</i>	<input type="checkbox"/> Temperature: <input type="checkbox"/> 105 (Ic) <input type="checkbox"/> 120 (IIc) <input type="checkbox"/> 140 (IIIc) <input type="checkbox"/> 160 (IVc) Tumble Dry: <input type="checkbox"/> Low <input type="checkbox"/> Normal <input type="checkbox"/> High Number of Cycles: Evaluate For: <input type="checkbox"/> Dim. Change <input type="checkbox"/> Pilling <input type="checkbox"/> Color Change <input type="checkbox"/> Wrinkling <input type="checkbox"/> Snagging <input type="checkbox"/> Seam Integrity Evaluation Frequency:
Dimensional Change to Home Laundering <i>AATCC 135</i>	<input type="checkbox"/> Temperature: <input type="checkbox"/> 80 <input type="checkbox"/> 105 <input type="checkbox"/> 120 <input type="checkbox"/> 140 Tumble Dry: <input type="checkbox"/> Low <input type="checkbox"/> Normal <input type="checkbox"/> High Number of Cycles: Evaluate For: <input type="checkbox"/> Dim. Change <input type="checkbox"/> Pilling <input type="checkbox"/> Color Change <input type="checkbox"/> Wrinkling <input type="checkbox"/> Snagging <input type="checkbox"/> Seam Integrity Evaluation Frequency:
Dynamic Seam Fatigue <i>ASTM D4033</i>	<input type="checkbox"/>
Elongation <i>ASTM D5034</i>	<input type="checkbox"/>
Martindale Pilling <i>ASTM D4970</i>	<input type="checkbox"/>
Martindale Abrasion <i>ASTM D4966</i>	<input type="checkbox"/> Number of Cycles:
Oil Repellency: Hydrocarbon <i>AATCC 118</i>	<input type="checkbox"/>
Random Tumble Pilling <i>ASTM D3512</i>	<input type="checkbox"/>
Seam Slippage <i>ASTM D434</i>	<input type="checkbox"/>
Seam Slippage <i>ASTM D4034</i>	<input type="checkbox"/>
Snagging Test Mace Method <i>ASTM D3939</i>	<input type="checkbox"/>
Stiffness <i>ASTM D4032</i>	<input type="checkbox"/>
Taber <i>ASTM D3884</i>	<input type="checkbox"/> Number of Cycles:
Tear Strength Tongue Method <i>ASTM D2261</i>	<input type="checkbox"/>
Tear Strength Trapezoid Method <i>ASTM D5733</i>	<input type="checkbox"/>
Water Repellency: Spray Test <i>AATCC 22</i>	<input type="checkbox"/>
Wet / Dry Crocking <i>AATCC 8</i>	<input type="checkbox"/>
Wyzenbeek <i>ASTM D4157</i>	<input type="checkbox"/> Cotton Duck <input type="checkbox"/> Wire Screen <input type="checkbox"/> Number of Cycles:
Other (Please Specify):	<input type="checkbox"/>

Pattern Name:	Color:
Lot Number:	Manufacturer:
Content:	
Notes:	